

(12) INTERNATIONAL APPLICATION PUBLISHED PURSUANT TO  
THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organisation  
International Bureau



(43) International publication date :  
5 February 2004 (05.02.2004)

PCT

(10) International publication number :  
WO 2004/012340 A2

(51) International patent classification : H03M 7/30,

(72) Inventors; and  
(75) Inventors/Applicants (for US only) : GUIONNET,  
Thomas [FR/FR]; 81, avenue Aristide Briand, F-35000  
Rennes (FR), GUILLEMOT, Christine [FR/FR]; 2, allée  
Françoise Dolto, F-35135 Chantepie (FR).

(21) International application number : PCT/FR2003/002246

(22) International filing date : 16 July 2003 (16.07.2003)

(74) Agent : PLACAIS, Jean-Yves; Cabinet Netter, 36, avenue  
Hoche, F-75008 Paris (FR).

(25) Language of filing : French

(81) Designated States (national) : JP, US.

(26) Language of publication : French

(84) Designated State (regional) : European Patent (AT, BE, BG,  
CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT,  
LU, MC, NL, PT, RO, SE, SI, SK, TR).

(30) Information relating to priority :  
02/09287 22 July 2002 (22.07.2002) FR  
03/03288 18 March 2003 (18.03.2003) FR

Published :


— without international search report; will be republished upon  
receipt of this report

(71) Applicants (for all Designated States except US): INRIA  
INSTITUT NATIONAL DE RECHERCHE EN  
INFORMATIQUE ET EN AUTOMATIQUE [FR/FR];  
Domaine de Voluceau, Rocquencourt, Boîte postale 105,  
F-78153 Le Chesnay Cedex (FR).

With regard to the two-letter codes and other abbreviations,  
refer to the "Explanatory notes on codes and abbreviations"  
appearing at the beginning of each regular edition of the PCT  
Gazette.

(54) Title : DEVICE AND METHOD FOR ROBUST DECODING OF ARITHMETIC CODES

(54) Titre : DISPOSITIF ET PROCEDE DE DECODAGE ROBUSTE DE CODES ARITHMETIQUES



(57) Abstract: The invention concerns a decoder (2) comprising a first input for receiving a coded flow of second binary elements (Yd). It comprises a second input for receiving channel properties (lc) designed to define probabilities of receiving second binary elements, upon transmitting first binary elements, a first module (12) defining a source model (8) adapted to define the probabilities for x-ary symbols associated with transitions between source states in a source state diagram, a so-called product model (7), adapted to define a correspondence between the x-ary symbols and the first binary elements produced in a product state diagram, a product state being a function of a source state, a processing module (6) adapted to calculate probabilities of decoding x-ary symbols, knowing bits of the coded flow of second binary elements from the channel properties (lc) of the source model (8) and of the product model (7), and adapted to reconstitute the most probable flow of x-ary symbols from said computed probabilities.

[Continued overleaf]

BEST AVAILABLE COPY

WO 2004/012340 A2